



January 2007

---

# Product Information



## **DELTRON** **Anti-Silicone Additive**

*Anti-Silicone Additive – D899*

### **PRODUCT DESCRIPTION**

Anti-silicone Additive D899 is an ancillary product specially formulated to help eliminating cratering problems due to silicone or grease contamination.

---

### **Application Guide**



Add 15ml of D899 to 1l of ready-for-use Deltron topcoat. This product should be added after activation and before thinning, to ensure that the maximum VOC for the product in use is not exceeded. Thinner should then be added to the normal recommended level.

---

### **PERFORMANCE AND LIMITATIONS**



Do **not** use D899 in Primers, Deltron BC and Envirobase. Excessive quantities of D899 cause sagging of the topcoat.

---

### **EQUIPMENT CLEANING**

After use, clean all equipment thoroughly with cleaning solvent or thinner.

---

## VOC INFORMATION

This product falls outside of the scope of EU Directive 2004/42 and therefore does not have a VOC product category classification. This product can be used by professional motor vehicle repairers.

---

## HEALTH AND SAFETY

**These products are for professional use only**, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose. For Health and Safety information please refer to the material Safety Data Sheet, also available at: [http://www.ppg.com/PPG\\_MSDS](http://www.ppg.com/PPG_MSDS)

**PPG Industries (UK) Limited.  
Auto Refinish  
Customer Service and Sales Group,  
Needham Road,  
Stowmarket,  
Suffolk.  
IP14 2AD, England.  
Tel: 01449 771775  
Fax: 01449 773480**

